

Sandwich panel SP2B E-PIR

Sandwich panel **SP2B E-PIR** is available in thicknesses 40 - 110 mm.

It is a perfect solution for most buildings and structures, combining **high quality** with **very good technical properties**.

The core of this sandwich panel is made of rigid, HCFC-free, self-extinguishing and sustainable polyisocyanurate foam (PIR). Its **excellent thermal insulation properties** enable the decrease of panel thickness which transfers directly to lower transportation and assembly costs, as well as **significant savings** of building's life cycle costs.

Applications:

- External walls
- Internal walls
- Ceilings



Properties

Model name	Sandwich panel SP2B E-PIR
Standard module width	1100 mm
Optional module width (B)	1000 (D = 80, 100, 110 mm)
Minimum length	2000 mm
Maximum Length	18500 mm
External facing thickness	0.5 mm
Internal facing thickness	0.4 mm
External Fire Exposure	NRO

Thickness D (mm)	40	60	80	100	110
Weight (kg/m ²)	10	10.8	11.5	12.3	12.6
U-value (W/m ² K)	0.56	0.36	0.27	0.22	0.20
Sound insulation Rw (dB)	24	24	24	24	24
Reaction to fire	B-s2, d0	B-s2, d0	B-s2, d0	B-s2, d0	B-s2, d0

Wall fire resistance values & max span horizontal / vertical orientation (m):	40	60	80	100	110
EI 15	-	-	-	7.5 / 7.5	7.5 / 7.5
EI 20	-	-	-	4.0 / 4.0	4.0 / 4.0

Detailed information regarding the application of fire resistance ratings can be obtained from Ruukki Sales.

All properties are declared in accordance with EN 14509 and related standards.

Coatings and colors

Materials


Fa cin g	Coating	Corrosivi ty categ ory	UV re sistan ce	Colours
Ext ern al	GreenCoat HIARC MA X	C4	Ruv4	RAL7035, RAL9006 (RR40), RAL9007 (RR41)
Ext ern al	Polyester	C3	Ruv 2-3	RAL1015, RAL3009 (RR29), RAL3013, RAL5005, RAL6011, RAL7015 (RR23), RAL7016 (RR288), RAL7035, RAL9002, RAL9006, RAL9007, RAL9010
Int ern al	Polyester	C3	-	RAL9002, RAL9010
Int ern al	PVC lamin ate *	C4	-	White

Facing		Corrosivity category
External	Stainless steel*	C5-I
Internal	Stainless steel*	C5-I


**) optional material*

UV resistance describes how well the coating is able to keep its original colour and gloss levels in accordance with EN10169. The higher the class, the better the resistance.


Corrosivity categories describe the outdoor climate conditions in accordance with EN12944. The higher the category, the more corrosive environment.




RAL1015 Light ivory




RAL 3009 Oxide red




RAL3013 Tomato red




RAL5005 Signal blue




RAL6011 Reseda green



RAL 7015 Slate grey




RAL7016 Anthracite grey




RAL7035 Light grey



RAL9002 Grey white



RAL9006 White aluminium



RAL9007 Grey aluminium



RAL9010 White

For external facings of 1000 mm module width only the following colors are available: RAL1015, RAL5005, RAL7015 (RR23), RAL7035, RAL9002, RAL9006, RAL9007, RAL9010.


Profile options



Ribbed R550




Ribbed R275



Linear L25




Linear L



Micro M



Flat F



Ribbed R28

Modular width	Facing	Profile options
1100mm	External	L, L25, M, R28, R275, R550, F
	Internal	L, L25, F
1000mm	External	L, L25, M
	Internal	L, L25

M profiling not available for panel thickness 80 mm, modular width 1000mm

L25 available only for panel thicknesses 80, 100, 110 mm.

Stainless steel available for panel thicknesses 60 mm. For stainless steel only L profiling is available.

Design tools



Traypan® software for designing sandwich panels

With TrayPan®, you can design metal faced sandwich panels made by Ruukki. A panel structure can be designed as a single- or multi-span construction. You can easily give, with a few parameters, both suction and pressure loads caused by the wind. The application also calculates the necessary fasteners.

[Go to Traypan®](#)

Download BIM objects to your desktop

ProdLib brings Ruukki products as BIM models directly to your desktop in 3D form for design programs AutoCAD, Autodesk Revit, Archicad and Tekla Structures. Product libraries compile all necessary design models and detailed drawings in one place. Library updates are automatically notified, so as a user you can be sure that your product information is constantly up to date. ProdLib can also be used as a standalone desktop application.

[Go to BIM library](#)

Technical documents

Here you can find all technical documents related to Ruukki's sandwich panels. Documents are organised by document type. Click to enter document library.

**Product
descriptions**



**Accessory
documents**



Load tables



**Installation
instructions**



**Maintenance
instructions**



**Sound insulation
values**



Certificates and approvals

Here you can find all certificates and approvals related to Ruukki's sandwich panels. Documents are organised by document type. Click to enter document library.

**Declaration of
performance**



**Environmental
product declaration**



**Intruder resistance
certificate**

