

Liberta Cor-Ten 700

Create a harmonious, rusty layout with Liberta Cor-Ten 700 for ventilated Cor-Ten facade systems.


Ruukki® Emotion

Available also with perforation and backlighting.




SEND CONTACT REQUEST

Properties



Model name	Liberta Cor-Ten 700
Depth	30 mm
Horizontal joint	10 mm
Vertical joint	20, 25, 30 mm
Fastening Style	Visible

Perforation layout



mm

а	≥10
b	≥10
C	≥ d+25
d	16, 20, 30, 40, 50, 60

Symmetrical perforation: Fully perforated in symmetrical square layout. Only 1 hole size (d) and distance (a, b, c) per product.

Art perforation: Fully or partly perforated in freely chosen locations. All hole sizes (d) and distances (c) available per product.

Size table



Size table Liberta Cor-Ten® 700

Material: COR-TEN® A steel 1.50 mm

Optimal size range:

- Width: 575...625 mm & 1050...1150 mm
 - Height: ≥ 1500 mm

Special size range:

- Width: 100...360 mm
- Height: 100...210 mm

Minimum sizes:

- Width: 150 mm
- Height: 150 mm

Materials

Material	Material thickness (mm)	Weight (kg/m ²)	Surface treatment	Reaction to fire
Steel Cor-Ten A *	1.5	13.6	-	A1

Due to its unique chemical composition, Cor-Ten weather-resistant structural steel sheet has a significantly better ability to resist atmospheric corrosion than similar general structural steels.

Weather-resistant steel is used in architectural applications without requiring any separate surface treatment. Use of weather-resistant steel thus eliminates the need for surface treatments during the manufacturing and operational periods, in turn lowering the environmental load and costs throughout the product's life cycle.

The weather resistance of the product is due to its oxide layer i.e. the patina which forms on the steel surface which is resistant to the action of alloys and has low oxygen permeability. The oxide layer is created when weather-resistant steel is wetted and dried repeatedly. The protective surface layer forms in normal weather conditions within 18...36 months. The patina layer is initially reddish brown in colour, becoming darker in tone over the course of time. In industrial environments the patina forms more rapidly on the steel and darkens more than in cleaner rural environments. The protective patina layer cannot form, however, if the surface of the steel is continuously damp or dirty.

Cor-Ten A grade steel is used for the manufacture of panels (S355J0WP-COR-TEN A).

BIM objects



Download BIM objects to your desktop

ProdLib brings Ruukki products as BIM models directly to your desktop in 3D form for design programs AutoCAD, Autodesk Revit, Archicad and Tekla Structures. Product libraries compile all necessary design models and detailed drawings in one place. Library updates are automatically notified, so as a user you can be sure that your product information is constantly up to date. ProdLib can also be used as a standalone desktop application.

Go to BIM library

Download documents

Ruukki Liberta rainscreen panels order form_2.2.4 XLSM, 4.5 MB

Declaration of performance

Ruukki Cor-Ten facades - Certification

Order form



Ruukki Liberta rainscreen panels order form_2.2.4 XLSM, 4.5 MB

Maintenance instructions



Ruukki Cor-Ten facades - maintenance instructions PDF, 70.3 KB



Ruukki powder coated facade claddings - Maintenance instructions PDF, 0.6 MB

L	_ . 🗅	
l	A	


Ruukki colour coated steel - Maintenance instructions PDF, 0.6 MB

Accessory documents



EN_Cladding_Accessories_02_2020 PDF, 3.6 MB

References



Tårnet Kulturarena office building in Norway

For this building we delivered a Ruukki Forma® façade system including sandwich panels and the façade claddings.




Modern apartment building in Estonia

The main entrance and parking spaces attract attention with Art perforated Liberta Cor-Ten 700 cassettes with backlighting. Rye straws fit to the surroundings p...



LUT University – Public construction

During the years 2016–2018, the main building of LUT University in Lappeenranta, specialising in technical and economic research and education, was completely o...



Varuste.net commercial building in Finland

"We have been installing Ruukki's products for a long time. The smoothness of installation work on the construction site was guaranteed by the coordination of d...